TITLE OF THE INVENTION

TASK ALLOCATION METHOD IN MULTIPROCESSOR SYSTEM, TASK ALLOCATION PROGRAM PRODUCT, AND MULTIPROCESSOR SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

5   This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2002-335632, filed November 19, 2002, the entire contents of which are incorporated herein by reference.

10   BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a task allocation method in a multiprocessor system having different kinds of processors with different instruction sets, a

15   task allocation program product, and a multiprocessor system.

2. Description of the Related Art

A multiprocessor system is a computer system that executes one program with a plurality of processors

20   (CPUs), as described, for example, in Chapter 9 of the Japanese translation of "Computer Organization and Design: The Hardware/Software Interface", 2nd ed. Vol. 2, David A. Patterson, John L. Hennessy, translated by Mitsuaki Narita, Nikkei BP, ISBN

25   4-8222-8057-8.

The respective processors are connected by an inter-processor connection unit such as a bus or a

crossbar switch. A shared memory and an I/O control
unit are connected to the inter-processor connection
unit. In many cases, each processor has a cache
memory. There is known a multiprocessor system wherein

5   a shared memory is not provided but each processor has
a local memory.

There is a widely used method of developing a
program to be executed on a multiprocessor system. In
this method, a program is described on the basis of the

10   dependency among tasks (hereinafter referred to as
"inter-task dependency"). A task is an execution unit
of a program that implements a set of processing. An
inter-task dependency refers to either of, or both of,
the transfer of data and transfer of control among

15   tasks. Each task is provided with a program module
necessary for actually executing the task on the
processor. This program development method has a
feature that a program can be reused in units of a
program module of each task. Thereby, the efficiency

20   of development of the program is enhanced, and
resources of many excellent program modules that have
previously been developed can be utilized.

When a program described on the basis of the
inter-task dependency is to be executed on a

25   multiprocessor system, a process is required to
allocate tasks to the respective processors by
determining which task is to be executed by which

processor. This task allocation process is performed so as to achieve high execution efficiency. The "high execution efficiency" means, for example, that the execution time of the entire program is short, the process data amount per unit time is large, the load on each processor is small, and the data amount in inter-processor communications is small (or the number of times of inter-processor communications is small).

The processor (CPU) has its own specific instruction set, depending on the kind of the processor. The instruction set is a group of instructions that can be understood by the processor. Aside from an ordinary multiprocessor system comprising the same kind of processors each having the same instruction set, there is a multiprocessor system comprising different kinds of processors having different instruction sets (hereinafter referred to as "hetero-multiprocessor system"). The hetero-multiprocessor executes a program formed by combining, as tasks, program modules described by a plurality of instructions sets for different kinds of processors.

As a matter of course, in the hetero-multiprocessor system, like the ordinary multiprocessor system comprising the same kind of processors, tasks are allocated to the processors so as to achieve high program execution efficiency. However, even if the task allocation method used in the ordinary

multiprocessor system is simply applied to the hetero-multiprocessor system, a sufficient program execution efficiency cannot be obtained.

In the normal multiprocessor system, an individual task is allocated to the processor having the same instruction set as is used for describing the program module of this task. If task allocation is performed in the hetero-multiprocessor system, using the task allocating method in the ordinary multiprocessor system as a standard for judgment, inter-processor communications will occur frequently due to the inter-task dependency, that is, due to the order of execution of tasks. Due to an overhead of such frequent inter-processor communications, a serious problem, that is, deterioration in program execution efficiency, occurs in the hetero-multiprocessor system.

The present invention is directed to a task allocation method in a multiprocessor system having different kinds of processors with different instruction sets, which can enhance program execution efficiency, and also to a task allocation program product and a multiprocessor system.

BRIEF SUMMARY OF THE INVENTION

According to embodiments of the present invention, there is provided a task allocation method, in a multiprocessor system having a first processor with a first instruction set and a second processor with a

second instruction set. A task is allocated to either
of the first processor or the second processor. The
task corresponds to a program having an execution
efficiency. The program includes a program module

5   described by either of the first instruction set or the
second instruction set. In the method, a task that
corresponds to a program module described by the first
instruction set is allocated to the first processor.
It is determined whether or not the execution

10   efficiency of the program is improved if a destination
allocated for the task is changed from the first
processor to the second processor. If the execution
efficiency of the program is improved, the destination
is changed to the second processor.

15   BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING
        FIG. 1 is a block diagram showing a structure of a
multiprocessor system according to embodiments of the
present invention;
        FIG. 2 shows a first example of implementation of

20   a task allocation program;
        FIG. 3 shows a second example of implementation of
a task allocation program;
        FIG. 4 shows a third example of implementation of
a task allocation program;

25   FIG. 5 shows a fourth example of implementation of
a task allocation program;
        FIG. 6 shows an example of a program described on

the basis of the dependency among tasks executed by the

multiprocessor system;

FIG. 7A shows an example of the state of execution

of a task;

5   FIG. 7B shows another example of the state of

execution of a task;

FIG. 7C shows still another example of the state

of execution of a task;

FIG. 8 is a block diagram showing a functional

10   configuration of a task allocation system;

FIG. 9 is a block diagram showing a detailed

structure of an optimization execution determination

section 25 shown in FIG. 8;

FIG. 10 shows an example of a program described on

15   the basis of the dependency among tasks, wherein the

tasks are created based on program modules described by

a plurality of different instruction sets;

FIG. 11 shows an example in which the program of

FIG. 10 is allocated to processors, employing the

20   instruction sets used for describing the program

modules as a standard for determination of allocation;

FIG. 12 shows an example of an allocation scheme,

wherein the allocation illustrated in FIG. 11 is

regarded as "provisional allocation" and the

25   provisional allocation destinations are properly

changed to determine final allocation;

FIG. 13 is a flowchart illustrating an example of

a task allocation process;

FIG. 14 is a flowchart illustrating an example of a provisional allocation process in the flowchart of FIG. 13;

FIG. 15 is a flowchart illustrating an example of a determination process in the flowchart of FIG. 13;

FIG. 16 shows an example of a pre-process of the determination process in FIG. 15;

FIG. 17 is a flowchart illustrating an example of an allocation destination processor changing process in FIG. 13;

FIG. 18 is a flowchart illustrating another example of the allocation destination processor changing process in FIG. 13;

FIG. 19 is a flowchart illustrating still another example of the allocation destination processor changing process shown in FIG. 13;

FIG. 20 is a flowchart illustrating another example of the task allocation process;

FIG. 21 is a flowchart illustrating still another example of the task allocation process;

FIG. 22A shows an example of a program module complex relating to a task allocation process according to embodiments of the present invention;

FIG. 22B shows another example of the program module complex;

FIG. 22C shows still another example of the

program module complex;

FIG. 23 is a flowchart illustrating an example of the provisional allocation process;

FIG. 24 is a flowchart illustrating an example of the allocation destination processor changing process;

FIG. 25 is a flowchart illustrating another example of the allocation destination processor changing process; and

FIG. 26 is a flowchart illustrating still another example of the allocation destination processor changing process.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments consistent with the present invention include a hetero-multiprocessor. This multiprocessor includes a plurality of kinds of processors with different instruction sets. When a plurality of tasks are to be executed, the multiprocessor realizes selection and allocation change of tasks which should more properly be allocated to processors with different instruction sets. Thereby, the program execution efficiency of the entire system is enhanced.

There is provided a method of allocating a plurality of tasks to a multiple processors in a multiprocessor system. The tasks correspond to a program to be executed. The system includes at least a first processor with a first instruction set and a second processor with a second instruction set. Of the

tasks, those described by the first instruction set are allocated to the first processor. At least one of the tasks allocated to the first processor is chosen as an object task, and it is determined whether the program execution efficiency is improved by changing the destination allocated for the object task to the second processor having the second instruction set. If the determination result indicates that the execution efficiency is improved, the allocation destination of the object task is changed to the second processor.

Specifically, the tasks executed by the multiprocessor system are created based on program modules each described by any one of the different instruction sets of the respective processors.

Embodiments consistent with the present invention provide a method and apparatus wherein tasks corresponding to a program are provisionally allocated to processors having the same instruction sets as those used in describing the program modules, and then it is determined whether the execution efficiency of the program is improved by changing the allocation destination processor. If the determination result indicates the necessity for the change of the allocation destination processor, the allocation destination of the object task is changed to implement final allocation.

Embodiments of the present invention will now be

described with reference to the accompanying drawings.
(Entire Structure of Multiprocessor System)

FIG. 1 shows an example of a basic structure of a multiprocessor system according to an embodiment of the present invention. This system is a so-called hetero-multiprocessor system. A plurality of processors 1 to 3 having instruction sets A, B and C, a shared memory 4 and an I/O control unit 5 are connected by an inter-processor connection unit 7 such as a bus or a crossbar switch. A large-capacity storage unit, such as a disk drive 6, is connected to the I/O control unit 5. A task allocation system 8, which is conceptually shown in FIG. 1, is connected to the inter-processor connection unit 7.

Although not shown in FIG. 1, the processors 1 to 3 may have caches or local memories. The multi-processor system may not have the shared memory. FIG. 1 shows three processors 1 to 3, but the number of processors may be two, or more than three. It is not necessary that all the processors included in the hetero-multiprocessor system have mutually different instruction sets. Two or more of the processors may have the same instruction set. In short, the hetero-multiprocessor system may include at least two kinds of processors having different instruction sets.

Program modules necessary for actually executing tasks on the processors 1 to 3, which correspond to the

program executed by the multiprocessor system, are stored in the disk drive 6 connected to the I/O control unit 5 or the shared memory 4. In the case of a multiprocessor system which does not have a shared memory but has local memories in processors, the program modules are stored in the local memories. In the program module, instructions necessary for executing the associated task are described by a specific instruction set.

(Examples of Implementation of Task Allocation System)

The task allocation system 8 functions to properly allocate tasks of a program, which is to be executed by the multiprocessor system, to the processors 1 to 3. Specifically, the task allocation system 8 is embodied as a program (hereinafter referred to as "task allocation program"). The task allocation program may be a dedicated program for task allocation, a part of an operating system, or a main program other than the operating system. FIGS. 2 to 5 show examples of implementation of the task allocation program.

In an example shown in FIG. 2, the task allocation program 12 is present as a part of an operating system (OS) 11 that runs on a specific processor 1. The task allocation program 12 controls a task allocation process for all the processors 1 to 3 including the processor 1 on which the operating system 11 including the task allocation program 12 runs.

In an example depicted in FIG. 3, the task
allocation program 12 is present as a part of each of
the operating systems 11 running on all the processors
1 to 3 included in the multiprocessor system. The
5   task allocation process in the system of FIG. 3 is
executable in two modes. In one mode, the task
allocation programs 12, which are parts of the
operating systems 11 running on the processors 1 to 3,
cooperate on a completely equal basis.

10   In the other mode of the task allocation process
shown in FIG. 3, the task allocation program, which is
a part of the operating system 11 running on a specific
one of the processors 1 to 3, is used as a main
program. The task allocation programs, which are parts
15   of the operating systems 11 running on the other
processors, are used as sub-programs. These main
program and sub-programs cooperate to execute the task
allocation process.

In an example shown in FIG. 4, a management
20   processor 9 is provided in addition to the principal
processors 1 to 3 in the multiprocessor system. The
task allocation program 12 is present as a part of an
operating system 13 running on the management processor
9. No task of the program executed by the multi-
25   processor system is allocated to the management
processor 9.

FIG. 5 shows an example in which the architectures

shown in FIGS. 3 and 4 are combined. The task
allocation program 12, which is a part of the operating
system 13 running on the management processor 9,
operates as a main program of the task allocation
5   program. The task allocation programs 12, which are
parts of the operating systems 11 running on the
processors 1 to 3, operate as sub-programs of the task
allocation program. The sub-programs cooperate with
the main program to execute the task allocation
10   process.

In the examples shown in FIGS. 2 to 5, as
described above, the task allocation program is a part
of the operating system. However, the task allocation
program can similarly be implemented as a part of a
15   main program or a dedicated program for task
allocation.

(Program Executed by the Multiprocessor System)

As is shown in FIG. 6, a program executed by the
multiprocessor system is described by a plurality of
20   tasks T1 to T6 and the dependency among the tasks T1 to
T6. As mentioned above, each of the tasks T1 to T6 is
an execution unit of a program that implements a set of
processing. The dependency among the tasks T1 to T6
refers to either of, or both of, the transfer of data
25   and transfer of control among the tasks T1 to T6. In
FIG. 6, the transfer of data or control from task to
task is indicated by arrows. When program modules of

tasks are executed, data is transferred among the
tasks, as indicated by the arrows.

(Examples of Execution of Task of Program)

FIGS. 7A to 7C show examples of the state of
5   execution of tasks.

An example shown in FIG. 7A relates to 1-input/
1-output task execution. The task execution comprises
three steps: receiving data necessary for processing
from an input-side task, subjecting the data to the
10   processing, and finally transmitting the processed data
to an output-side task.

An example of FIG. 7B relates to 2-input/2-output
task execution. The task execution comprises receiving
data from all input-side tasks, processing the received
15   data, and transmitting the processed data to output-
side tasks.

In an example shown in FIG. 7C, unlike FIGS. 7A
and 7B, input data is not received at a time. In the
task execution in FIG. 7C, data is intermittently
20   received from input-side tasks. For example, data
received in a given unit time is processed, and the
processed data is transmitted to an output-side task in
succession.

The cost of the data reception/transmission among
25   tasks during the task execution is relatively high,
though it depends on configurations of the multi-
processor system.

In the multiprocessor system having the shared memory 4 as shown in FIG. 1, regardless of whether a task of transmitting data and a task of receiving data are allocated to the same processor or different processors, the data transmission is realized by data write to the shared memory 4, and the data reception is realized by data read-out from the shared memory 4. In general, the cost of write/read to/from the shared memory 4 is also high.

On the other hand, in the multiprocessor system wherein processors have caches, if the tasks of data transmission and data reception are allocated to the same processor, the data transmission/reception among the tasks is performed via the cache in the processor. Normally, the access to the cache is faster than the access to the shared memory. Thus, if attention is paid to the tasks, the transmission of processed data and the reception of data necessary for processing are realized by the data read/write from/to the cache, and the apparent cost of data transmission/reception is reduced. However, the content in the cache needs to be kept in consistent with the content in the memory and, in fact, data write to the shared memory occurs.

In the case where the task of data transmission and the task of data reception are allocated to different processors, the data transmission is realized by data write to the shared memory and the data

reception is realized by data read-out from the shared memory, though the data transmission/reception mode may differ depending on the architecture of the caches. The data transmission/reception among the tasks is thus realized. The cost of the data transmission/reception via the shared memory in this case is also high.

In the multiprocessor system wherein the processors have local memories, if the tasks for data transmission and data reception are allocated to the same processor, the data transmission/reception among the tasks is performed using the local memories in the processors. Normally, the access to the local memory is faster than the access to the shared memory. However, in the case where the task for data transmission and the task for data reception are allocated to different processors, the inter-task data transmission/reception is realized by data transfer from the local memory of the processor, to which the transmission-side task is allocated, to the local memory in the processor, to which the reception-side task is allocated. Normally, the cost of the communication between the local memories is high, like the case of the access to the shared memory.

As stated above, in the multiprocessor system, the cost of inter-processor communication is high. It is thus necessary to allocate tasks to processors, giving full consideration to the inter-processor

communication.

In the prior-art task allocation scheme, a task is allocated to the processor having the same instruction set as is used for the description of the program module necessary for executing the task. If this allocation method is applied to the hetero-multiprocessor system, inter-processor data communications will occur frequently and the program execution efficiency deteriorates.

In order to alleviate this problem, the status of "provisional allocation" is given to the conventional allocation scheme in which a task is allocated to a processor having the same instruction set as is used for describing the program module necessary for executing the task. After the completion of the "provisional allocation", the allocation of tasks to the processors is changed and optimized to enhance the program execution efficiency.

(Details of Task Allocation System)

FIG. 8 shows an example of the structure of the task allocation system 8 shown in FIG. 1. As described above, the task allocation system 8 may be a dedicated task allocation program, a part of an operating system, or a main program other than the operating system. In FIG. 8, the functions of the task allocation system 8 are depicted in blocks for easier understanding.

In FIG. 8, a task provisional allocation section

21 performs the aforementioned "provisional allocation". That is, the task provisional allocation section 21 allocates a task to the processor having the same instruction set as is used for describing the

5   program module necessary for executing the task. Information relating to provisional allocation of each task is stored, for example, in the disk drive 6 shown in FIG. 1, or a provisional allocation task storage section 22, which is a part of the shared memory 4.

10 The information relating to provisional allocation of each task is read out by a provisional allocation task read-out section 23.

The information read out by the provisional allocation task read-out section 23 is input to a to-

15 be-optimized task determination section 24. With respect to all tasks corresponding to each program to be executed by the multiprocessor system, the to-be-optimized task determination section 24 determines whether it is better to change allocation destinations

20 by the optimization. With respect to a task that has been determined to be a to-be-optimized task, an optimization execution determination section 25 determines whether the allocation of the task to the processor should actually be changed by the

25 optimization.

An optimization execution section 26 actually performs an allocation destination changing process for

the task, for which the change of the allocation destination to the processor by the optimization has been determined. Regardless of whether the allocation destination has been changed or not, an allocation task write section 27 writes information on a final allocation result of all tasks, for example, into the disk drive 6 shown in FIG. 1 or an allocation task storage section 28, which is a part of the shared memory 4.

As is shown in FIG. 9, the optimization execution determination section 25 includes, as means for estimating program execution efficiency, e.g. an execution time estimation section 31, a unit-time processible data amount estimation section 32, a processor load estimation section 33 and an inter-processor communication data amount estimation section 34. An estimation method selection section 35 selects one or more of the estimation sections for determining execution efficiency.

The execution time estimation section 31 estimates task execution times in a case where the object task is allocated, without change, to a provisional allocation destination and in a case where the allocation destination is changed. The unit-time processible data amount estimation section 32 estimates a processible data amount per unit time of the program in cases where the object task is allocated, without change, to a

provisional allocation destination and the allocation
destination is changed. The processor load estimation
section 33 estimates a load on the allocation-
destination processor in the case where the object task
allocation destination is changed. The inter-processor
communication data amount estimation section 34
estimates an inter-processor communication data amount
of the program in cases where the object task is
allocated, without change, to a provisional allocation
destination and the allocation destination is changed.

An execution efficiency determination section 36
determines the program execution efficiency on the
basis of an estimation result of the estimation
section(s) selected by the estimation method selection
section 35. Specifically, the execution efficiency
determination section 36 determines whether the program
execution efficiency is enhanced by the change of the
task allocation destination, on the basis of (a)
whether the execution time estimated by the execution
time estimation section 31 decreases by the change of
the allocation destination, (b) whether the processible
data amount estimated by the unit-time processible data
amount estimation section 32 increases by the change of
the allocation destination, or whether the estimated
processible data amount increases beyond a
predetermined threshold by the change of the allocation
destination, (c) whether a load on the processor

estimated by the processor load estimation section 33 becomes an overload, and (d) whether the inter-processor communication data amount estimated by the inter-processor communication data amount estimation section 34 decreases by the change of the allocation destination.

When the estimation method selection section 35 has selected a plurality of estimation sections, the execution efficiency determination section 36 comprehensively examines the estimation results of these estimation sections, and finally determines whether the execution efficiency is enhanced. Concrete methods of the execution efficiency determination are explained later in detail.

An allocation destination processor determination section 37 determines a new allocation destination processor for the task, with respect to which the execution efficiency determination section 36 has determined that "the program execution efficiency is enhanced by the change of the task allocation destination." On the other hand, the provisional allocation destination processor is determined to be the final allocation destination processor for the task, with respect to which the execution efficiency determination section 36 has determined that "the program execution efficiency is not enhanced by the change of the task allocation destination."

FIG. 10 shows an example of a program in which program modules described by a plurality of instruction sets for different processors are combined as tasks T1 to T9. The instruction sets, by which the program modules of tasks T1 to T9 are described, are designated by letters A, B and C in parentheses (). The program shown in FIG. 10 comprises tasks T1, T5 and T9 having program modules described by the instruction set A, tasks T2 and T6 having program modules described by the instruction set B, and tasks T3, T4, T7 and T8 having program modules described by the instruction set C.

According to a conventional task allocation method, the tasks in the program shown in FIG. 10 are allocated to the processors having the instruction sets, by which the associated program modules are described, as shown in FIG. 11. Specifically, the tasks T1, T5 and T9 are allocated to the processor 1 having the instruction set A. The tasks T2 and T6 are allocated to the processor 2 having the instruction set B. The tasks T3, T4, T7 and T8 are allocated to the processor 3 having the instruction set C.

As mentioned above, the status of "provisional allocation" is given to the task allocation shown in FIG. 11. By the optimization after the provisional allocation, the allocation destination processors can be changed, for example, as shown in FIG. 12. Thereby, the number of times of inter-task data

transmission/reception, which requires inter-processor communications, is greatly reduced from seven, as shown in FIG. 11, to two, as shown in FIG. 12. In short, an overhead due to inter-processor communications

5   decreases, and the program execution efficiency is remarkably improved.

(Task Allocation Process Procedure 1)

A task allocation process procedure will now be described with reference to flowcharts. FIG. 13

10   illustrates a basic flow of an example of the task allocation process. The procedure shown in FIG. 13 is referred to as task allocation process procedure 1.

The task provisional allocation section 21 (shown in FIG. 8) provisionally allocates all tasks of the

15   program to the respective processors (step S11). The information relating to the provisional allocation of each task is retained in the provisional allocation task storage section 22 (shown in FIG. 8). The information relating to the provisional allocation is

20   read out from the provisional allocation task storage section 22 by the provisional allocation task read-out section 23. The read-out information is delivered to the to-be-optimized task determination section 24.

The to-be-optimized task determination section 24

25   determines an object task (to-be-optimized task), from all the tasks of the program, which will possibly enhance the program execution efficiency by the change

of the allocation destination processor. With respect
to the determined object task, the optimization
execution determination section 25 determines whether
the program execution efficiency is enhanced by

5   the change of the allocation destination processor
(step S12).

As regards the task which has been determined in
step S12 not to enhance the program execution
efficiency by the change of the allocation destination

10   processor, the present process is finished by setting
the provisional allocation destination processor,
obtained in step S11, to be the final allocation
destination processor. On the other hand, for the task
which has been determined to enhance the program

15   execution efficiency by the change of the allocation
destination processor, a new allocation destination
processor is determined.

Next, the allocation destination processor of the
task, which has been determined to enhance the program

20   execution efficiency by the change of the allocation
destination processor, is changed to the determined new
allocation destination processor (step S13). Specifi-
cally, to change the allocation destination processor
means to acquire the program module described by the

25   instruction set possessed by the new allocation
destination processor for the object task.

Following the completion of the process

illustrated in FIG. 13, all tasks of the program are allocated to proper processors. Thereby, the multiprocessor system can efficiently execute the present program.

The process comprising steps S11 to S13 in FIG. 13 is described in detail.

FIG. 14 shows the details of the processing of step S11 in FIG. 13. The instruction set, by which the program module of the object task to be allocated is described, is determined (step S101). The object task is allocated to the processor having the determined instruction set (step S102). Referring to the program shown in FIG. 10 by way of example, the tasks of the program shown in FIG. 10 are allocated to the processors, as shown in FIG. 11, in this provisional allocation step.

FIG. 15 is a flowchart illustrating the details of the processing of step S12 in FIG. 13. FIG. 15 refers to the process for one object task, but in fact all the tasks are subjected to the same process. This process can be applied twice or more to the same object task. For example, it is possible to perform the process of FIG. 15 for all the tasks, perform allocation change for some tasks by optimization, and then perform the same process for the resultant tasks once again. Thereby, a better optimization result may be obtained.

The information relating to the task provisional

allocation, which is read out by the provisional
allocation task read-out section 23, is delivered to
the to-be-optimized task determination section 24.
The to-be-optimized task determination section 24

5   determines whether a task, which is present immediately
before or immediately after the object task of interest
subjected to the provisional allocation in step S11, is
allocated to a processor having an instruction set
different from the instruction set of the processor

10   to which the object task is provisionally allocated
(step S201).

In the program of FIG. 10, for instance, there is
no task immediately before each of tasks T1, T2, T4 and
T5. In this case, a pseudo task is defined as

15   "immediately preceding task." The pseudo task is, for
example, a task, with respect to which an estimated
execution time is "0", data to be transmitted to the
object task is "0" and there is no influence on the
load of the processor. Similarly, an "immediately

20   following task" is defined for the object task, such as
task T9 in FIG. 10, immediately after which there is no
task.

If "YES" in step S201, the information relating to
the object task, which is the to-be-optimized task, is

25   delivered to the to-be-optimized task determination
section 24, and a process in step S202 is performed.
On the other hand, if "NO" in step S201, that is, if

tasks immediately before and after the object task are provisionally allocated to the same processor as the object task, there is no need to change the allocation destination processor for the object task. In other words, even if the allocation destination processor is changed, the program execution efficiency is not improved. Accordingly, this determination result is sent to the allocation task write section 27, and the information relating to the provisional allocation task is written in the allocation task storage section 28. The process is thus finished.

In step S202, the optimization execution determination section 25 estimates the program execution efficiency in two cases, i.e. a case where the task determined to be the to-be-optimized task in step S201 is allocated, without change, to the processor to which task is already provisionally allocated, and a case where the task determined to be the to-be-optimized task in step S201 is allocated to a candidate processor for allocation destination change. The candidate processor for allocation destination change, in this context, is any one of the processors that are different from the processor, to which the to-be-optimized task of interest is provisionally allocated, and is any one of the processors to which the tasks immediately before and after the to-be-optimized task of interest are provisionally allocated.

Subsequently, the optimization execution determination section 25 determines whether the program execution efficiency is enhanced by changing the allocation destination processor of the to-be-optimized object task to the candidate processor for allocation destination change (step S203). If "YES" in step S203, the optimization execution determination section 25 determines that the candidate processor for allocation destination change is the final allocation destination processor (step S204) and attaches a mark, which indicates that the allocation destination processor is to be changed to the determined allocation destination processor, to the to-be-optimized object task (step S205). Thus, the process is finished. If "NO" in step S203, the process is finished without further processing.

(Grouping of Tasks)

It is possible that the program is not such a simple one as shown in FIG. 10. In the case of a large-scale program with many tasks, a program with a complex inter-task dependency or a program with many tasks and with a complex inter-task dependency, it is likely that the processing in the to-be-optimized task determination section 24 and optimization execution determination section 25 becomes complex.

FIG. 16 illustrates a process for grouping tasks of the program, thereby simplifying the task allocation

process for the complex program. This process is
provided, for example, as a pre-process of step S201 in
FIG. 15. The grouping of tasks can simplify the task
provisional allocation, and accordingly simplify the
process shown in FIG. 15. FIG. 16 shows the process
for one task by way of example, but in fact the same
process is performed for all the tasks.

The flow of the process in FIG. 16 is described.
To start with, it is determined whether there is a
task(s) immediately after the object task of interest
(step S211). If "YES" in step S211, it is determined
whether all the task(s) immediately after the object
task are allocated to the same processor as the object
task (step S212).

If "YES" in step S212, the task, which is
immediately after the object task and is preceded by
only the object task, is selected (step S213). The
selected task and the object task are grouped (step
S214), and the group is handled as a single object
task. The group is delivered to step S201 in FIG. 15.
By this grouping, the task allocation process can
easily be performed even for a complex program.
(Optimization Execution Determination)

Next, the process of determination step S12 in
FIG. 13, in particular, the process in steps S202 and
S203 in FIG. 15, is described. The optimization
execution determination section 25 (shown in FIG. 8),

the structure of which is shown in detail in FIG. 9,
performs the process by using singly or in combination
the following execution efficiency determination
standards.

5   [Execution Efficiency Determination Standard 1]

It is determined whether the program execution
time (the time needed for executing tasks) is decreased
by the change of the allocation destination processor.

The time needed for executing tasks can be
10   estimated from the instruction sequence described in
the program module necessary for task execution.
Similarly, the time needed for executing tasks in the
candidate processor for allocation destination change
can be estimated.

15   According to the execution efficiency
determination standard 1, if the estimated execution
time needed for executing the object task, which is
allocated to the candidate processor for allocation
destination change, is shorter than the estimated
20   execution time needed for executing the object task
which is allocated, without change, to the provisional
allocation processor, the object task is determined to
be the to-be-optimized task, that is, the task for
which the allocation destination processor should be
25   changed by optimization.

It is possible that the estimated execution time
needed for executing the object task in a plurality of

candidate processors for allocation destination change
is shorter than the estimated execution time needed for
executing the object task in the provisional allocation
processor. In this case, the processor with a shortest

5   estimated execution time may be chosen as the alloca-
tion change destination processor. Alternatively,
according to the execution efficiency determination
standard 1, a plurality of processors may be chosen as
candidate processors for allocation destination change,

10   and then the final allocation change destination
processor may be determined on the basis of another
execution efficiency determination standard.
[Execution Efficiency Determination Standard 2]

It is determined whether the data amount

15   processible by the task within a unit time is increased
by the change of the allocation destination processor.

The data amount processible by the task within the
unit time means a data amount that is receivable by the
task from a preceding task within the unit time. The

20   data amount receivable from the preceding task within
the unit time by the inter-task communication is
affected by whether the object task of interest and
each preceding task are provisionally allocated to the
same processor or to different processors. The reason

25   is that communication between different processors is
very high in cost than communication within the same
processor.

According to the execution efficiency determination standard 2, the data amount receivable within the unit time by inter-task communications with all preceding tasks is estimated in two cases, i.e. a case where the object task is allocated, without change, to the provisional allocation destination processor, and a case where the object task is allocated to each candidate processor for allocation destination change.

If the data amount receivable within the unit time in any one of candidate processors for allocation destination change is larger than the data amount receivable within the unit time in the current provisional allocation destination processor, it is determined that the allocation destination processor for the object task of interest should be changed to the candidate processor for allocation destination change.

It is possible that the data amount receivable within the unit time by the object task of interest, which is allocated to a plurality of candidate processors for allocation destination change, is larger than the data amount receivable within the unit time by the object task of interest, which is allocated, without change, to the current provisional allocation processor. In such a case, a processor with a largest data amount receivable within the unit time by the

object task is chosen as the processor for allocation destination change.

In the execution efficiency determination standard 2, the following method is adoptable. That is, a plurality of processors are chosen as candidate processors for allocation destination change, taking into account a case where, for example, the data amount receivable within the unit time by the object task in a plurality of candidate processors for allocation destination change is the same, and is larger than the data amount receivable within the unit time by the object task in the provisional allocation processor. Then, the final allocation destination processor is chosen on the basis of another execution efficiency determination standard.

[Execution Efficiency Determination Standard 3]

It is determined whether the increment of the data amount processible by the task within a unit time, between the case where the allocation destination processor is changed and the case where the allocation destination processor is not changed, is larger than a preset threshold.

The execution efficiency determination standard 3 is basically the same as the execution efficiency determination standard 2. In the determination standard 3, a threshold is used when the data amount receivable within the unit time by the object task of

interest, which is allocated to the provisional
allocation processor, is compared with the data amount
receivable within the unit time by the object task of
interest, which is allocated to the candidate processor

5   for allocation destination change. Specifically, a
static threshold preset before the start of selection
or a dynamic threshold dynamically set during selection
is adopted with respect to the data amount receivable
within the unit time.

10   In the case where the data amount receivable
within the unit time by the object task of interest,
which is allocated to the candidate processor for
allocation destination change, is larger than the data
amount receivable within the unit time by the object

15   task of interest, which is allocated to the provisional
allocation processor, and is also larger than the
threshold, it is determined that the allocation
destination processor for the object task should be
changed to the candidate processor for allocation

20   destination change.
[Execution Efficiency Determination Standard 4]
It is determined whether a load on the processor
for allocation destination change becomes an overload
due to the change of the allocation destination

25   processor.
Even where the allocation destination processor is
changed from the provisional allocation processor, if

an overload occurs in the processor for allocation destination change, the execution efficiency of the entire program is not improved.

The load on all the processors, in the case where the task of interest is allocated, with no change, to the provisional allocation processor, is estimated. In addition, the load on all the processors, in the case where the task of interest is allocated to any one of the candidate processors for allocation destination change, is estimated. If the allocation destination is changed and no overload occurs in the candidate processor for allocation destination change, it is determined that the allocation destination processor should be changed by optimization.

It is possible that there are a plurality of candidate processors for allocation destination change and no overload on the processors occurs even if the allocation destination is changed to any one of the candidate processors. In such a case, the following method may be adopted. That is, a candidate processor for allocation destination change, which causes a least load variation, is chosen. Alternatively, a candidate processor for allocation destination change, which causes a least load variation even if the allocation destination of the object task of interest is changed, is chosen. Moreover, in the execution efficiency determination standard 4, a plurality of processors may

be chosen as candidate processors for allocation

destination change, and the final allocation

destination processor may be chosen on the basis of

another execution efficiency determination standard.

5   [Execution Efficiency Determination Standard 5]

It is determined whether the inter-processor

communication data amount of the entire program is

reduced by the change of the allocation destination

processor.

10   The key in the improvement of program execution

efficiency in the multiprocessor system is the inter-

processor communication data amount. Paying attention

to this point, a determination standard is set as to

whether the amount of data transferred between

15   processors in the entire program is reduced when the

object task is allocated, without change, to the

provisional allocation processor and when the object

task is allocated to the candidate processor for

allocation destination change.

20   Specifically, the amount of data transferred by

inter-processor communication in the entire program is

estimated in a case where the allocation destination

processor of the object task of interest is unchanged

and in a case where the allocation destination

25   processor of the object task is changed to any one of

the candidate processors for allocation destination

change. If the amount of data transferred by

inter-processor communication in the entire program is reduced by changing the allocation destination processor of the object task to any one of the candidate processors for allocation destination change, it is determined that the allocation destination processor for the object task should be changed to the candidate processor for allocation destination change.

It is possible that the estimated amount of data transferred by inter-processor communication in the entire program in the case where the allocation destination of the object task is changed to a plurality of candidate processors for allocation destination change is less than the estimated amount of data transferred by inter-processor communication in the entire program in the case where the object task is allocated, with no change, to the provisional allocation processor. In such a case, a candidate processor for allocation destination change, which requires a least amount of data transferred by inter-processor communication in the entire program, is chosen as the allocation change destination processor. Alternatively, in the execution efficiency deter-mination standard 5, a plurality of processors may be chosen as candidate processors for allocation destination change, and the final allocation destination processor may be chosen on the basis of another execution efficiency determination standard.

[Execution Efficiency Determination Standard 6]

It is determined whether the inter-processor communication data amount of the entire program in the unit time is reduced by the change of the allocation destination processor.

The execution efficiency determination standard 6 is basically the same as the execution efficiency determination standard 5. In the determination standard 6, the inter-processor transfer data amount in the unit time is estimated in a case where the object task of interest is allocated, without change, to the provisional allocation processor and in a case where the allocation destination processor of the object task is changed to any one of the candidate processors for allocation destination change. If the amount of data transferred by inter-processor communication in the unit time in the entire program in the case where the allocation destination processor of the object task is changed to any one of the candidate processors for allocation destination change is less than the amount of data transferred by inter-processor communication in the unit time in the entire program in the case where the object task is allocated, without change, to the provisional allocation processor, it is determined that the allocation destination processor for the object task should be changed to the candidate processor for allocation destination change.

(Examples of Task Allocation Process)

The above-described task allocation process procedures are explained referring to examples of specific programs.

5   In the description below, the procedures for optimizing the allocation destinations of tasks T1 to T9 of the program shown in FIG. 10, which are provisionally allocated as shown in FIG. 11, are explained in detail. The program shown in FIG. 10

10   comprises tasks T1, T5 and T9 having program modules described by the instruction set A, tasks T2 and T6 having program modules described by the instruction set B, and tasks T3, T4, T7 and T8 having program modules described by the instruction set C.

15   In the provisional allocation (FIG. 11) of tasks of the program shown in FIG. 10, the tasks T1, T5 and T9 are allocated to the processor 1 having the instruction set A, the tasks T2 and T6 are allocated to the processor 2 having the instruction set B, and the

20   tasks T3, T4, T7 and T8 are allocated to the processor 3 having the instruction set C.

In the examples of the task allocation process described below, only the execution efficiency determination standards 1 and 5 are used in determining

25   whether the allocation destination processor is to be changed, and in determining which processor is chosen as the allocation destination processor. Assume that a

higher priority is given to the execution efficiency determination standard 5 than to the execution efficiency determination standard 1. These assumptions appear to be reasonable since it would be difficult to prepare all the above-described execution efficiency determination standards 1 to 6 due to constraints on system configurations, etc. in the actual multi-processor system.

[Optimization of Allocation Destination of Task T1]

<Step 1-1> Task T1 is read out.

<Step 1-2> Since only a pseudo task is present immediately before task 1, the immediately preceding task can be ignored.

<Step 1-3> Tasks T2 and T3 are present immediately after task T1, and tasks T2 and T3 are provisionally allocated to the processors 2 and 3 different from the processor 1 to which task 1 is provisionally allocated. It is thus determined whether the allocation destination of task T1 is to be changed.

<Step 1-4> It is estimated whether the inter-processor communication data amount of the entire program is decreased by changing the allocation destination of task T1 from the processor 1 to processor 2, 3.

<Step 1-5> An estimated required execution time in a case where task T1 is executed, without change, by the processor 1, and an estimated required execution time in a case where task T1 is executed by the candidate

processor 2, 3 for allocation destination change, are calculated.

<Step 1-6> Assume that the result in step 1-4 shows that there is no variation in inter-processor communication data amount of the program before and after the change of the allocation destination, and also assume that the result in step 1-5 shows that the estimated required execution time is shorter in the case where task T1 is executed on the processor 1.

<Step 1-7> Based on the result in step 1-6, it is determined that the allocation destination processor for task T1 is not changed.

[Optimization of Allocation Destination of Task T2]

<Step 2-1> Task T2 is read out.

<Step 2-2> Task T1 is present immediately before task 2.

<Step 2-3> Task T3 is present immediately after task T2, and tasks T1 and T3 are provisionally allocated to the processors 1 and 3 different from the processor 2 to which task 2 is provisionally allocated. It is thus determined whether the allocation destination of task T2 is to be changed.

<Step 2-4> It is estimated whether the inter-processor communication data amount of the entire program is decreased by changing the allocation destination of task T2 from the processor 2 to processor 1, 3.

<Step 2-5> An estimated required execution time in a

case where task T2 is executed, without change, by the processor 2, and an estimated required execution time in a case where task T2 is executed by the candidate processor 1, 3 for allocation destination change, are calculated.

<Step 2-6> Assume that the result in step 2-4 shows that there is no variation in inter-processor communication data amount of the program before and after the change of the allocation destination, and also assume that the result in step 2-5 shows that the estimated required execution time is shorter in the case where task T2 is executed on the processor 1.

<Step 2-7> Based on the result in step 2-6, it is determined that the allocation destination processor for task T2 is changed to the processor 1.

[Optimization of Allocation Destination of Task T3]

<Step 3-1> Task T3 is read out.

<Step 3-2> Tasks T1 and T2 are present immediately before task T3.

<Step 3-3> Task T7 is present immediately after task T3, and tasks T1 and T2 are allocated to the processor 1 different from the processor 3 to which task T3 is provisionally allocated. Task T7 is provisionally allocated to the processor 3. Since tasks T1 and T2 are provisionally allocated to the processor 1, it is thus determined whether the allocation destination of task T3 is to be changed.

<Step 3-4> It is estimated whether the inter-processor communication data amount of the entire program is decreased by changing the allocation destination of task T3 to the processor 1.

<Step 3-5> An estimated required execution time in a case where task T3 is executed, without change, by the processor 3, and an estimated required execution time in a case where task T3 is executed by the candidate processor 1 for allocation destination change, are calculated.

<Step 3-6> Assume that the result in step 3-4 shows that the inter-processor communication data amount of the entire program is decreased by changing the allocation destination of task T3 to the processor 1, because tasks T1 and T2 are already allocated to the processor 1. In addition, assume that the result in step 3-5 shows that the estimated required execution time is substantially the same even in the case where task T3 is executed on the processor 1.

<Step 3-7> Based on the result in step 3-6, it is determined that the allocation destination processor for task T3 is changed to the processor 1.

[Optimization of Allocation Destination of Task T4]

<Step 4-1> Task T4 is read out.

<Step 4-2> Since only a pseudo task is present immediately before task 4, the immediately preceding task can be ignored.

<Step 4-3> Task T6 is present immediately after task T4, and task T6 is provisionally allocated to the processor 2 different from the processor 3 to which task 4 is provisionally allocated. It is thus

5   determined whether the allocation destination of task T4 is to be changed.

<Step 4-4> It is estimated whether the inter-processor communication data amount of the entire program is decreased by changing the allocation destination of

10   task T4 to the processor 2.

<Step 4-5> An estimated required execution time in a case where task T4 is executed, without change, by the processor 3, and an estimated required execution time in a case where task T4 is executed by the candidate

15   processor 2 for allocation destination change, are calculated.

<Step 4-6> Assume that the result in step 4-4 shows that the inter-processor communication data amount of the entire program is decreased by changing the

20   allocation destination of task T4 to the processor 2. In addition, assume that the result in step 4-5 shows that the estimated required execution time is substantially the same even in the case where task T4 is executed on the processor 2.

25   <Step 4-7> Based on the result in step 4-6, it is determined that the allocation destination processor for task T4 is changed to the processor 2.

[Optimization of Allocation Destination of Task T5]

<Step 5-1> Task T5 is read out.

<Step 5-2> Since only a pseudo task is present immediately before task 5, the immediately preceding task can be ignored.

<Step 5-3> Task T6 is present immediately after task T5, and task T6 is provisionally allocated to the processor 2 different from the processor 1 to which task 5 is provisionally allocated. It is then determined whether the allocation destination of task T5 is to be changed.

<Step 5-4> It is estimated whether the inter-processor communication data amount of the entire program is decreased by changing the allocation destination of task T5 to the processor 2.

<Step 5-5> An estimated required execution time in a case where task T5 is executed, without change, by the processor 1, and an estimated execution time in a case where task T5 is executed by the candidate processor 2 for allocation destination change, are calculated.

<Step 5-6> Assume that the result in step 5-4 shows that the inter-processor communication data amount of the entire program is decreased by changing the allocation destination of task T5 to the processor 2. Also assume that the result in step 5-5 shows that the estimated required execution time increases if task T5 is executed on the processor 2.

<Step 5-7> Based on the result in step 5-6 and the priority preset before the start of the process, it is determined that the allocation destination processor for task T5 is changed to the processor 2.

[Optimization of Allocation Destination of Task T6]

<Step 6-1> Task T6 is read out.

<Step 6-2> Tasks T4 and T5 are present immediately before task 6. Since both tasks T4 and T5 are allocated to the same processor 3 as task T6, these tasks can be ignored.

<Step 6-3> Task T8 is present immediately after task T6, and task T8 is provisionally allocated to the processor 3 different from the processor to which task 6 is provisionally allocated. It is thus determined whether the allocation destination of task T6 is to be changed.

<Step 6-4> It is estimated whether the inter-processor communication data amount of the entire program is decreased by changing the allocation destination of task T6 to the processor 3.

<Step 6-5> An estimated required execution time in a case where task T6 is executed, without change, by the processor 2, and an estimated execution time in a case where task T6 is executed by the candidate processor 3 for allocation destination change, are calculated.

<Step 6-6> Assume that the result in step 6-4 shows that the inter-processor communication data amount of

the entire program increases if the allocation
destination of task T6 is changed to the processor 3.
In addition, assume that the result in step 6-5 shows
that the estimated required execution time increases if
task T6 is executed on the processor 3.

<Step 6-7> Based on the result in step 6-6, it is
determined that the allocation destination processor
for task T6 is not changed.

[Optimization of Allocation Destination of Task T7]

<Step 7-1> Task T7 is read out.

<Step 7-2> Task T3 is present immediately before task
T7. Task T3 is allocated to the processor different
from the processor 3 to which task T7 is allocated.

<Step 7-3> Task T8 is present immediately after task
T7, and task T8 is allocated to the same processor 3 as
task T7. However, since task T3 immediately before
task T7 is allocated to the processor 1 different from
the processor 3 to which task T7 is allocated, it is
determined whether the allocation destination of task
T7 is to be changed.

<Step 7-4> It is estimated whether the inter-processor
communication data amount of the entire program is
decreased by changing the allocation destination of
task T7 to the processor 1.

<Step 7-5> An estimated required execution time in a
case where task T7 is executed, without change, by the
processor 3, and an estimated required execution time

in a case where task T7 is executed by the candidate

processor 1 for allocation destination change, are

calculated.

<Step 7-6> Assume that the result in step 7-4 shows

that the inter-processor communication data amount

of the entire program increases if the allocation

destination of task T7 is changed to the processor 1.

In addition, assume that the result in step 7-5 shows

that the estimated required execution time increases if

task T7 is executed on the processor 1.

<Step 7-7> Based on the result in step 7-6, it is

determined that the allocation destination processor

for task T7 is not changed.

[Optimization of Allocation Destination of Task T8]

<Step 8-1> Task T8 is read out.

<Step 8-2> Tasks T6 and T7 are present immediately

before task T8. Task T6 is allocated to the processor

3 different from the processor 3 to which task T8 is

allocated.

<Step 8-3> Task T9 is present immediately after task

T8, and task T9 is allocated to the processor 1

different from the processor 3 to which task T8 is

allocated. It is thus determined whether the

allocation destination of task T8 is to be changed.

<Step 8-4> It is estimated whether the inter-processor

communication data amount of the entire program is

decreased by changing the allocation destination of

task T8 to the processor 1, 2.

<Step 8-5> An estimated required execution time in a
case where task T8 is executed, without change, by the
processor 3, and an estimated required execution time
in a case where task T8 is executed by the candidate
processor 1, 2 for allocation destination change, are
calculated.

<Step 8-6> Assume that the result in step 8-4 shows
that the inter-processor communication data amount of
the entire program is unchanged even if the allocation
destination of task T8 is changed to the processor 1 or
2. In addition, assume that the result in step 8-5
shows that the estimated required execution time is
shortest if task T8 is executed, without change, on the
processor 3.

<Step 8-7> Based on the result in step 8-6, it is
determined that the allocation destination processor
for task T8 is not changed.

[Optimization of Allocation Destination of Task T9]

<Step 9-1> Task T9 is read out.

<Step 9-2> Task T8 is present immediately before task
T9. Task T8 is allocated to the processor 3 different
from the processor 1 to which task T9 is allocated.

<Step 9-3> Since only a pseudo task is present
immediately after task T9, it can be ignored. However,
since task T8 immediately before task T9 is allocated
to the processor 3 different from the processor 1 to

which task T9 is allocated, it is determined whether
the allocation destination of task T9 is to be changed.

<Step 9-4> It is estimated whether the inter-processor
communication data amount of the entire program is
decreased by changing the allocation destination of
task T9 to the processor 3.

<Step 9-5> An estimated required execution time in a
case where task T9 is executed, without change, by the
processor 1, and an estimated required execution time
in a case where task T9 is executed by the candidate
processor 3 for allocation destination change, are
calculated.

<Step 9-6> Assume that the result in step 9-4 shows
that the inter-processor communication data amount of
the entire program is decreased by changing the
allocation destination of task T9 to the processor 1.
In addition, assume that the result in step 9-5 shows
that the estimated required execution time becomes
shorter if task T9 is executed on the processor 3.

<Step 9-7> Based on the result in step 9-6, it is
determined that the allocation destination processor
for task T9 is changed to the processor 3.

As a result of the above task allocation process,
the allocation of the tasks of the program (shown in
FIG. 10) provisionally allocated as shown in FIG. 11 is
optimized as shown in FIG. 12.

(Acquisition of Program Module for Allocation
Destination Processor)

A description is given of a process of acquiring a
program module for an allocation change destination
processor in the optimization execution section
(allocation destination processor changing section) 26
shown in FIG. 8.

In order to execute the task, whose allocation
destination processor has been changed by the above-
described process, it is necessary to acquire, by some
method, a program module for the allocation destination
processor. The program module necessary for executing
the task whose allocation destination processor has
been changed, is described by the instruction set
possessed by the provisionally allocated processor.
This instruction set is different from the instruction
set possessed by the changed allocation destination
processor.

In the present example, any one of the three
procedures illustrated in FIGS. 17 to 19 is used to
acquire the program module for executing the task and
is described by the instruction set possessed by the
changed allocation destination processor. FIGS. 17 to
19 illustrate in detail the process of step S13 in
FIG. 13.

In the procedure shown in FIG. 17, the
instructions peculiar to the instruction set possessed

by the provisional allocation processor, which is used
to describe the program module originally possessed by
the object task, are replaced with instructions for
executing the same process as with the instruction set
of the changed allocation destination processor.
Thereby, the program module described by the
instruction set possessed by the changed allocation
destination processor is obtained.

To start with, it is determined whether the
instructions in the program module of the object task,
whose allocation destination has been determined to
be changed, are absent or not in the allocation
destination processor (step S301). If "YES" in step
S301, the instructions are replaced with instructions
for executing the same process as with the instruction
set of the allocation destination processor, thereby
generating a program module for the allocation
destination processor (step S302). If "NO" in step
S301, there is no need to acquire a new program module,
and the process is finished. The processing in steps
S301 and S302 is repeated until the completion of
the processing for all instructions is determined in
step S303.

FIG. 18 illustrates a process substituted for step
S302 in FIG. 17. The procedure of this process uses a
compiler capable of generating a program module
described by the instruction set possessed by the

changed allocation destination processor, on the basis
of the source code of the program module originally
possessed by the object task. Thereby, the program
module described by the instruction set possessed by
the changed allocation destination processor is
acquired.

FIG. 19 also illustrates a process substituted for
step S302 in FIG. 17. In the procedure of this
process, the program module of the object task
described by the instruction set possessed by the
changed allocation destination processor is obtained by
a search through the file system or the network.
(Task Allocation Process Procedure 2)

Next, another example of the task allocation
process procedure is described. FIG. 20 illustrates
the flow of task allocation process procedure 2.

In the task allocation process procedure 1 shown
in FIG. 13, all tasks are provisionally allocated to
the respective processors (step S11). It is determined
whether the program execution efficiency is enhanced by
changing the allocation destination processor (step
S12). The allocation destination processor for the
object task, which has been determined to enhance
the program execution efficiency by the change of
the allocation destination processor, is changed
(step S13).

On the other hand, in the task allocation process

procedure 2 shown in FIG. 20, one of the tasks is selected (step S21). The selected task is subjected to the processing corresponding to steps S11 to S13 in FIG. 13 (steps S22 to S24). The processing in steps S21 to S24 is repeated until the completion of the allocation process for allocating all tasks to the processors is determined.

If the process shown in FIG. 20 is completed, all the tasks of the program are properly allocated to the processors. Therefore, the multiprocessor system can efficiently execute the program.

(Task Allocation Process Procedure 3)

FIG. 21 illustrates the flow of still another task allocation process procedure. In this task allocation process procedure 3, all the tasks are provisionally allocated, as in step S11 in FIG. 13, following which the execution of the program is started (steps S31 and S32). Thereafter, only when a predetermined condition is satisfied in step S33 during the execution of the program, the processing corresponding to steps S12 and S13 in FIG. 13 is performed (steps S34 and S35). The processing in steps S33 to S35 is repeated until the completion of the execution of the program is determined in step S36.

Some examples of the "predetermined condition" in step S33 are as follows.

[Condition 1] An interrupt by the system timer, which

comes at regular intervals, has occurred.

[Condition 2]   A notice indicative of possible overload

has been issued from a certain processor.

[Condition 3]   An interrupt has occurred from a

processor in an idle state.

[Condition 4]   A notice has been issued from a certain

processor that the certain processor has issued an

input/output instruction and initiated an execution

completion wait state for the input/output instruction.

[Condition 5]   A certain processor has issued a notice

to the effect that execution of one task is completed.

Examples other than Conditions 1 to 5 are

possible.

(Program Module Complex)

Other embodiments of the present invention will

now be described.

In the above-described embodiments, the program to

be executed by the hetero-multiprocessor system is a

program described based on the inter-task dependency.

Moreover, each task, as shown in FIG. 10, is created

based on only the program module described by the

instruction set for a specific processor.

However, it is not necessary that each task of the

program to be executed by the hetero-multiprocessor

system is a single program module. Of all the tasks,

at least one task may be created based on a complex

including a plurality of program modules (hereinafter

referred to as "program module complex") described by
instruction sets possessed by two or more kinds of
processors.

For example, a program module complex 40A shown in
FIG. 22A includes program modules 41, 42, and 43
described by instruction sets A, B and C. A program
module complex 40B shown in FIG. 22B includes program
modules 41 and 42 described by instruction sets A
and B.

Each of the tasks of the program is given as a
program module complex shown in FIG. 22A or 22B, or as
a single program module 41 shown in FIG. 22C, depending
on, e.g. the content of the task or the intention of
the creator of the task.

All the tasks of the program may be given as
program module complexes each including a plurality of
program modules described by a plurality of common
instruction sets. In other words, each of the tasks
may be created based on a program module complex, for
example, as shown in FIG. 22A.

In the case where the above-described structure of
the program module complex is applied to the task, it
is preferable to set, as a prerequisite standard, a
determination standard "a program module described by
an instruction set possessed by an allocation
destination processor is present in a program module
complex of the object task", in addition to the

aforementioned execution efficiency determination standards. The reason is that unless the program module described by the instruction set possessed by the candidate processor for allocation destination change is present in the program module complex of the object task, the object task cannot be executed on the changed allocation destination processor even if the allocation destination processor is changed.

Next, a description is given of the processing in steps S11 and S13 in FIG. 13 in the case where at least one of the tasks is created based on the above-described program module complex.

FIG. 23 illustrates in detail the process corresponding to step S11 in FIG. 13. The instruction set, which is used to describe the program module in the program module complex of the object task to be allocated, is determined (step S111). The object task is allocated to the processor having the determined instruction set (step S112).

Some examples of the process procedure corre-sponding to step S13 in FIG. 13 are described with reference to FIGS. 24 to 26.

In the process procedure shown in FIG. 24, it is determined whether the allocation destination processor determined in step S12 in FIG. 13 is a processor using any one of the instruction sets of the program modules included in the program module complex of the object .

task (step S311). If "YES" in step S311, the program
module described by the instruction set is acquired
from the program module complex (step S312).

On the other hand, if "NO" in step S311, a given
one of the program modules included in the program
module complex of the object task is selected
(step S313). Then, like step S302 in FIG. 17, the
instructions in the program module of the task
described by the instruction set selected in step S313
are replaced with instructions for executing the same
process as with the instruction set of the allocation
destination processor, thereby generating a program
module for the allocation destination processor
(step S314).

In the process procedure in FIG. 25, the
processing in steps S321 to S323 is the same as the
processing in steps S311 to S313. The processing in
step S324 alone is different. If "NO" in step S321, a
given one of the program modules included in the
program module complex of the object task is selected
(step S323).

Like the process shown in FIG. 18, a compiler is
used which is capable of generating a program module
described by the instruction set possessed by the
changed allocation destination processor, on the basis
of the source code of the program module selected in
step S323. Thereby, the program module described by

the instruction set possessed by the changed allocation destination processor is acquired.

In the process procedure in FIG. 26, the processing in steps S331 and S332 is the same as the processing in steps S311 and S312. The processing in step S334 alone is different. If "NO" in step S331, the control advances to step S334, and the program module of the object task described by the instruction set possessed by the changed allocation destination processor is obtained by a search through the file system or the network.

As has been described above, even in the case where a task is created based on the program module complex, the task allocation according to embodiments of the present invention is effective.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.